



Medium-duty Solvent Cleaner & Degreaser

PRODUCT DESCRIPTION:

Pro-Struct Cleaner Degreaser is a concentrated alkaline cleaning solution designed to remove grease, oil and other contaminants. With adjustable dilution levels, this versatile medium-duty degreaser is ideal for industrial use. It ensures surfaces are clean and prepared for further treatment or coating application.

PRIMARY APPLICATIONS:

- Cleans grease, oil and similar contaminants
- Prepares surfaces for coatings
- General residential, commercial and industrial cleaning

FEATURES & BENEFITS:

- Concentrated alkaline
- Heavy to light residues
- Multiple surface applications

DIRECTIONS FOR USE:

Mixing:

Dilution guidelines based on soiling level:

Heavy soiling: As supplied or diluted 1:1 with water.

Medium soiling: Diluted 1:4 with water.

Light soiling: Diluted 1:10 with water.

Application:

For small areas, use a medium bristle brush. For large areas, use a soft bristle broom or foam generator. Rinse thoroughly with potable water to remove all residue before coating.

CAUTION: Always mix in plastic containers, not metal. Always add Pro-Struct Cleaner Degreaser to water, not vice versa.

Application:

- For small areas, use a medium bristle brush.
- For large areas, use a soft bristle broom or foam generator.
- Rinse thoroughly with potable water to remove all residue before coating.

STORAGE:

Store in a dry, cool area between 4°C to 65°C in tightly sealed containers.

TYPICAL PROPERTIES AT 25°C

Composition	Synthetic detergents & organic solvents
Packaging	5 Litre
Consistency	Liquid
Colour(s)	Fluorescent Yellow
Application Method	Medium bristle brush, soft bristle broom or spray
Coverage / Spread Rate / Yield	10m ² /litre of mixed ready-to-use solution (depending on soil to be removed and application equipment)
Cleaner	Water
Shelf Life	24 Months minimum when stored at 25°C



PRO-STRIES CLEANER DEGREASER

CLEAN-UP AND SAFETY:

Pro-Struct Cleaner Degreaser should be used in a well-ventilated area. In case of accidental spillage, dilute with water and run to an approved waste. In case of contact with skin and eyes, flush adequately with water. In severe eye cases, obtain medical attention.

TECHNICAL INFORMATION:

	Typical Result
VOC's	5g/litre
Density	1.00