

Crack filler

TYPICAL PROPERTIES AT 25°C

PRODUCT DESCRIPTION:

Pro-Struct Crack Filler is a lightweight, resin-bound compound designed to repair cracks and minor surface defects in plaster, concrete and masonry. With excellent water and UV-resistance, it creates a long-lasting, durable finish. Pro-Struct Crack Filler is easy to apply and matches the texture of standard plaster surfaces.

PRIMARY APPLICATIONS:

- Interior and exterior
- Repair plaster and brick surface cracks
- Correct concrete wall defects
- Fill minor masonry imperfections

FEATURES & BENEFITS:

- Ready-mixed
- Flexible crack bridging
- Low shrinkage
- Water and UV-resistant
- Easy trowelling
- Non-slumping
- Long open time
- Matches plaster finish

DIRECTIONS FOR USE:

Preparation:

Open the crack in a V-shape. Make sure the surface is clean, dry and free from dust or loose debris.

Application:

Use a putty knife or trowel to fill and compact the cracks. Smooth the surface with a damp trowel for an even finish. Alternatively, allow the Pro-Struct Crack Filler to dry before sanding smooth with fine sandpaper.

Drying:

Allow to dry for 1 hour at 25°C. Ensure the area is completely dry before sanding or applying additional coats.

RESISTANCE:

Once dry, the “Crack Filler” has excellent water and UV resistance and is unaffected by the cyclic temperature changes.

STORAGE:

Store in a cool, dry place away from heat sources.

CLEAN-UP AND SAFETY:

Avoid contact with skin and eyes. Wear gloves and goggles during application. Clean tools and spills immediately with water.

Composition	Resin-bound filler
Packaging	500 grams and 1kg
Finish	Smoothed, trowelled plaster
Colour(s)	Off-White
Application Method	Trowel or putty knife
Apply Over	Dust- and oil-free masonry and wood surfaces
Application Temperature	10°C to 35°C
Coverage / Spread Rate / Yield	1m ² /litre at 1mm thick
Drying / Curing Time	1 Hour at 25°C
Thinner	Water
Shelf Life	12 Months when stored properly