

CONSEAL CEMENTITIOUS COATING

EXCELLENT ADHESION

REPELS WATER

APPROXIMATE COLOUR AND APPEARANCE OF CONCRETE

GIVES EVEN APPEARANCE TO PATCHY AND IRREGULAR OFF-SHUTTER CONCRETE

PRINCIPAL USES

As a cementitious coating over concrete, bricks and blocks.

RESISTANCE

Excellent weather resistance. Does not check, crack or powder.

SPECIFICATION

Surfaces to be coated with Pro-Struct 511 at a rate of 1,5-2,0m²/lt/coat, dependant on surface profile.

INSTRUCTIONS

Surface must be clean, sound and free of shutter oil, curing compound, etc. Prior to application, the surface should be cleaned with a wire brush and thoroughly soaked with water. Dampening to be maintained immediately ahead of application to avoid ravelling.

Pro-Struct 511 Conseal is a two part kit – the 2 litre liquid being mixed with 6 litres of water before adding to the powder. This is mixed to a typical smooth slurry. Apply by block brush, ensuring mix is continuously stirred to avoid setting.

CAUTION

Under no circumstances should the 2 litre binder be added directly to the dry powder mix.

STORAGE

Store under dry conditions in accordance with SABS specification for cement.

TYPICAL PROPERTIES AT 25°C

Colour	Light grey non-uniform cementitious colour
No. of Components	2 + water
Mixing Ratio	Mix entire kit
Yield	16 Litres
Coverage	1,5-2,0m ² /litre/coat
Apply Over	Concrete or bricks and blocks
No. of Coats Required	1-2 Depending on surface profile and porosity
Apply By	Block brush
Thinners	Water
Cleaning	Water